

IN THE CLAIMS:

Please amend the claims as shown below.

1. (Currently Amended) An image processing apparatus for quantizing input image data, the apparatus comprising:

a bit connection component that connects a decimal portion of corrected image data of a preceding pixel output from a latch component, to input image data of a target pixel as lower bits of the image data of the target pixel, and outputs the bit-connected image data of the target pixel, wherein the bit-connected image data has an integer portion of the image data of the target pixel and the decimal portion of image data of the preceding pixel;

a correction component that generates corrected image data of the target pixel by adding a correction value to the bit-connected image data of the target pixel;

the latch component that latches a decimal portion of the corrected image data generated by the correction component of the target pixel by splitting-off, prior to performing quantization of the corrected image data, the decimal portion of the corrected image data from an integer portion of the corrected image data, output by the correction component, the spit-off and latched decimal portion to be connected to image data of a next pixel by the bit connection component, wherein the latch does not latch the without latching an integer portion of the corrected image data of the target pixel;

a quantization component that receives an integer portion of the corrected image data without receiving the decimal portion of the corrected image data of the target

pixel, and quantizes the received integer portion of the corrected image data of the target pixel;

an inverse quantizing component that inverse-quantizes the quantized integer portion of the corrected image data of the target pixel, and outputs an inverse-quantized data of the target pixel;

a calculation component that outputs a quantization error of the target pixel based on a difference between the integer portion of the corrected image data of the target pixel and the inverse-quantized data of the target pixel;

a buffer that stores the calculated quantization error; and

an error diffusion component that generates a correction value by diffusing the quantization error stored in said buffer,

wherein the correction value to be added to the bit-connected image data of the target pixel in said correction component is generated by said error diffusion component based on the calculated quantization errors of neighboring pixels of the target pixel stored in said buffer and diffusion coefficients being smaller than 1.0.

2. (Canceled)

3. (Previously Presented) The apparatus according to claim 1, further comprising a stop component that stops propagating the correction value in a case in which it is inappropriate to propagate the correction value to next and subsequent pixels.

4. (Previously Presented) The apparatus according to claim 1, further comprising:

a clear component that clears the decimal portion held in said latch component in a case in which it is inappropriate to connect the decimal portion of the correction value, which is latched in said latch component, to the lower bit side of the next input image data.

5. (Original) The apparatus according to claim 4, further comprising a processing limit component that limits clearing by said clear component when a scanning direction of the input image is reversed.

6. (Original) The apparatus according to claim 3, wherein the case in which it is inappropriate to propagate the correction value to next and subsequent pixels includes at least one of a case in which a pixel of interest is a start pixel of a line, a case in which the pixel of interest has a value equal to a lower limit level of the input image, and a case in which the pixel of interest has a value equal to an upper limit level of the input image.

7. (Original) The apparatus according to claim 1, further comprising a numerical value limit component that limits the quantization error calculated by said calculation component to a numerical value within a predetermined range.

8. to 19. (Canceled)

20. (Currently Amended) A method for quantizing input image data implemented in an image processing apparatus comprising a processor and a memory, the method comprising:

the processor performing the steps of:

a bit connection step of connecting a decimal portion of corrected image data of a preceding pixel output from a latch component, to input image data of a target pixel as lower bits of the image data of the target pixel, and outputting the bit-connected image data of the target pixel, wherein the bit-connected image data has an integer portion of the image data of the target pixel and the decimal portion of image data of the preceding pixel;

a correction step of generating corrected image data of the target pixel by adding a correction value to the bit-connected image data of the target pixel;

a latch step of latching, by the latch component, a decimal portion of the corrected image data generated by the correction component of the target pixel by splitting-off, prior to performing quantization of the corrected image data, the decimal portion of the corrected image data from an integer portion of the corrected image data, output by the correction step, the spit-off and latched decimal portion to be connected to the image data of the next pixel by the bit connection step, wherein the latch component does not latch the without latching an integer portion of the corrected image data of the target pixel;

a quantization step of receiving an integer portion of the corrected image data without receiving the decimal portion of the corrected image data of the target pixel, and quantizing the received integer portion of the corrected image data of the target pixel;

an inverse quantizing step of inverse-quantizing the quantized integer portion of the corrected image data of the target pixel, and outputting an inverse-quantized data of the target pixel;

a calculation step of outputting a quantization error of the target pixel based on a difference between the integer portion of the corrected image data of the target pixel and the inverse-quantized data of the target pixel;

a storing step of storing the calculated quantization error of the target pixel in a buffer; and

an error diffusion step of generating a correction value by diffusing the quantization error stored in said buffer,

wherein the correction value to be added to the bit-connected image data of the target pixel in said correction step is generated by said error diffusion step based on the calculated quantization errors of neighboring pixels of the target pixel stored in said buffer and diffusion coefficients being smaller than 1.0.

21. (Canceled)

22. (Previously Presented) The method according to claim 20, further comprising a step of stopping propagation of the correction value in a case in which it is inappropriate to propagate the correction value to next and subsequent pixels.

23. (Previously Presented) The method according to claim 20, further comprising the step of:

clearing the decimal portion held in said latching step in a case in which it is inappropriate to connect the decimal portion of the correction value, which is latched in said latch step, to the lower bit side of the next input image data.

24. (Previously Presented) The method according to claim 23, further comprising a step of limiting the clear process of said clear step when a scanning direction of the input image is reversed.

25. (Original) The method according to claim 22, wherein the case in which it is inappropriate to propagate the correction value to next and subsequent pixels includes at least one of a case in which a pixel of interest is a start pixel of a line, a case in which the pixel of interest has a value equal to a lower limit level of the input image, and a case in which the pixel of interest has a value equal to an upper limit level of the input image.

26. (Previously Presented) The method according to claim 20, further comprising a step of limiting the quantization error calculated in said calculation step to a numerical value within a predetermined range.

27. to 38. (Canceled)

39. (Currently Amended) A computer-readable storage medium on which is stored a computer-executable program for implementing a method for quantizing input

image data executed by an image processing apparatus, the program comprising the steps of:

a bit connection step of connecting a decimal portion of corrected image data of a preceding pixel output from a latch component, to input image data of a target pixel as lower bits of the image data of the target pixel, and outputting the bit-connected image data of the target pixel, wherein the bit-connected image data has an integer portion of the image data of the target pixel and the decimal portion of image data of the preceding pixel;

a correction step of generating corrected image data of the target pixel by adding a correction value to the bit-connected image data of the target pixel;

a latch step of latching, by the latch component, a decimal portion of the corrected image data generated by the correction component of the target pixel by splitting-off, prior to performing quantization of the corrected image data, the decimal portion of the corrected image data from an integer portion of the corrected image data, output by the correction step, the split-off and latched decimal portion to be connected to the image data of the next pixel by the bit connection step, wherein the latch component does not latch the ~~without latching~~ an integer portion of the corrected image data of the target pixel;

a quantization step of receiving an integer portion of the corrected image data without receiving the decimal portion of the corrected image data of the target pixel, and quantizing the received integer portion of the corrected image data of the target pixel;

an inverse quantizing step of inverse-quantizing the quantized integer portion of the corrected image data of the target pixel, and outputting an inverse-quantized data of the target pixel;

a calculation step of outputting a quantization error of the target pixel based on a difference between the integer portion of the corrected image data of the target pixel and the inverse-quantized data of the target pixel;

a storing step of storing the calculated quantization error in a buffer; and

an error diffusion step of generating a correction value by diffusing the quantization error stored in said buffer,

wherein the correction value to be added to the bit-connected image data of the target pixel in said correction step is generated by said error diffusion step based on the calculated quantization errors of neighboring pixels of the target pixel stored in said buffer and diffusion coefficients being smaller than 1.0.

40. to 61. (Canceled)